



ATELIER VALS
OUTDOOR ELEMENTS

Atelier Vals tiles are handcrafted concrete pavers composed of fine aggregates, portland cement, and white silica sand in several size and color options. Pavers are manufactured to a $\pm 1/16$ " tolerance, providing a consistent product facilitating easy installation in a variety of applications.

Application

Atelier Vals Tiles can be installed in any pedestrian application including patios, pools, porches, and walkways as well as limited, low-speed vehicular areas. Atelier Vals benefits include a high strength pavement that resists freeze/ thaw, are heat resistant, and are non-slip.

Technical Data

Compressive Strength – 7,000 psi (*Meets or Exceeds ASTM C39*)

Slip Resistance Coefficient of Friction – 0.89 (*Meets or Exceeds ASTM C1028*)

Water Absorption – less than 4% (*Meets or Exceeds ASTM C1195*)

Solar Reflectivity (SRI) - .75 varies based on color (*Meets or Exceeds ASTM C1549*)

Freeze Thaw – less than 1% loss of dry weight (*Meets or Exceeds ASTM 1260*)

** Test reports available upon request*

Standard Sizes

48x48

48x24

64x18

36x36

36x24

36x18

24x24

24x12

12x12

Standard Finishes

Terrazzo (TZ), Sand/ Smooth (SS), Thermal (TR), Non-Vibratory (NV)

Custom Patterns and Custom Pieces to specification