



Atelier Vals tiles are handcrafted concrete pavers composed of fine aggregates, portland cement, and white silica sand in several size and color options. Pavers are manufactured to a $\pm 1/16$ " tolerance, providing a consistent product facilitating easy installation in a variety of applications.

Application

Atelier Vals Tiles can be installed in any pedestrian application including patios, pools, porches, and walkways as well as limited, low-speed vehicular areas. Atelier Vals benefits include a high strength pavement that resists freeze/ thaw, are heat resistant, and are non-slip.

Technical Data

Compressive Strength – 10,000 psi (*Meets or Exceeds ASTM C39*)
Slip Resistance Coefficient of Friction – 0.89 (*Meets or Exceeds ASTM C1028*)
Water Absorption – less than 4% (*Meets or Exceeds ASTM C1195*)
Solar Reflectivity (SRI) - .75 varies based on color (*Meets or Exceeds ASTM C1549*)
Freeze Thaw – less than 1% loss of dry weight (*Meets or Exceeds ASTM 1260*)
** Test reports available upon request*

Standard Sizes

48x48
48x24
64x18
36x36
36x24
36x18
24x24
24x12
12x12

Standard Finishes

Terrazzo (TZ), Sand/ Smooth (SS), Thermal (TR), Non-Vibratory (NV)

Custom Patterns and Custom Pieces to specification