



Atelier Vals tiles are handcrafted concrete pavers composed of fine aggregates, portland cement, and white silica sand in several size and color options. Pavers are manufactured to a  $\pm 1/8$ " tolerance, providing a consistent product facilitating easy installation in a variety of applications.

### **Application**

Atelier Vals Tiles can be installed in any pedestrian application including patios, pools, porches, and walkways as well as limited, low-speed vehicular areas. Atelier Vals benefits include a high strength pavement that resists freeze/ thaw, are heat resistant, and are non-slip.

### **Technical Data**

Compressive Strength – 10,000 psi (*Meets or Exceeds ASTM C39*)  
Slip Resistance Coefficient of Friction – 0.89 (*Meets or Exceeds ASTM C1028*)  
Water Absorption – less than 4% (*Meets or Exceeds ASTM C1195*)  
Solar Reflectivity (SRI) - .75 varies based on color (*Meets or Exceeds ASTM C1549*)  
Freeze Thaw – less than 1% loss of dry weight (*Meets or Exceeds ASTM 1260*)

*\* Test reports available upon request*

### **Standard Sizes**

48x48  
48x24  
64x18  
36x36  
36x24  
36x18  
24x24  
24x12  
12x12

### **Standard Finishes**

Terrazzo (TZ), Sand/ Smooth (SS), Thermal (TR), Non-Vibratory (NV)

*Custom Patterns and Custom Pieces to specification*